



## **WILLIAM JOHNSTON** & COMPANY LIMITED

Glasgow Tel: +44 (0) 141 620 1666 | Inverness Tel: +44 (0) 1463 238 673  
[sales@williamjohnston.co.uk](mailto:sales@williamjohnston.co.uk) | [www.williamjohnston.co.uk](http://www.williamjohnston.co.uk)

ACM VAMAC WJ127



### **Black Commercial 2 ply EP80 Fabric insertion SBR Rubber 85° shore**

#### **WJ127**

**Black Commercial quality 2 ply EP80 Fabric Insertion SBR 80°** is a Commercial Grade, Commercial Quality Styrene Butadiene rubber blend with an EP80 fabric insertion.

**N.B. All our sheeting can be supplied plain or with self-adhesive backed tape (SAB). Rubber Strip to bespoke sizes are available along with customised sheets/gaskets. Please email your enquiry details to**

- Material Profile: See
- below Thickness: 0.5mm to 50mm
- Sheet Size: 1.4m wide in
- 10m rolls Finish: Smooth (SS)
- Cutting: Standard press-tools

Other grades, colours and finishes are available  
– subject to minimum batch quantities

## TECHNICAL DATA

STOCK ROLL SIZES [M X M X MM]	SURFACE FINISH	WEIGHT [KG/M2]
6mm x 1400mm x 10m	SS	9.96

## SPECIFICATIONS COMPOUND

SPECIFICATIONS COMPOUND	VALUES [TYPICAL]
Colour	Black

SPECIFICATIONS COMPOUND	VALUES [TYPICAL]
Compound	SBR
Density [specific gravity]	1.60
Hardness [Degrees Shore A]	85° ± 5°
Tensile Strength Kg/cm2 [Polymer]	40
Elongation at break	175
Minimum Temperature	-20°C
Maximum temperature	+70°C

### Disclaimer

Please note, failure to select the correct materials or products we supply ("the Products") may result in damage to plant, equipment or property. In some instances, it may cause death or personal injury. We are not designers and do not give advice about design related matters concerning the Products. We can help and assist with the technical specifications for the Products. In specific applications, particularly where critical conditions exist, we will try to assist you within the limitations of the services that we offer. All information supplied by us is intended as technical co-operation outlining the specifications of the different Products which we supply. To the extent permitted in law, no warranty is given in respect of any information supplied by us. The customer must satisfy themselves as to the suitability of the Products for their intended application and use. The correct fitting of Products is the responsibility of the customer. Your statutory rights remain unaffected. Save in respect of death, personal injury or fraud, our entire liability to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by our insurers.